

MALTA



Sleek exterior stainless steel or aluminium illuminated handrail system with concealed continuous downward light distribution.



microPrim™


Luminaire Structure

- Aluminium or stainless steel body
- Single cable entry
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- High-efficiency PMMA lens
- Remote driver is not included
- Standard unit length is 1 m, different lengths are available upon request
- All handrails and components are delivered completely pre-assembled for on-site installation
- LIGMAN prepares project handrail solutions according to layout drawings, elevations and project's brief, offering an end-to-end solution from concept through to implementation

Feature



Optic



Product colour



Special finishes upon request



MALTA

Technical information

| | Model number | Light source | Power | Lumen | Optic | CCT / CRI | Dimming type | Weight |
|--|------------------|--------------|-------|--------------|--------------|---------------------------------------|--------------|----------|
| Without remote driver - Constant voltage (CV) 24 V - Aluminium - IP20 | | | | | | | | |
| MALTA 4 | MAT-30031 | 120 LED/m | 9 W | 337 - 362 lm | G [60°x111°] | 3000K CRI80, 4000K CRI80, 5700K CRI80 | On/Off | 2.1 kg/m |
| Without remote driver - Constant voltage (CV) 24 V - Aluminium - IP65 | | | | | | | | |
| MALTA 3 | MAT-30021 | 120 LED/m | 9 W | 303 - 325 lm | G [60°x111°] | 3000K CRI80, 4000K CRI80, 5700K CRI80 | On/Off | 2.1 kg/m |
| Without remote driver - Constant voltage (CV) 24 V - Aluminium - IP65 - RGBW | | | | | | | | |
| MALTA 3 | MAT-30023 | 84 LED/m | 15 W | 365 - 373 lm | G [60°x111°] | RGBW30, RGBW40 | DMX, DMX/RDM | 2.1 kg/m |
| Without remote driver - Constant voltage (CV) 24 V - Aluminium - IP65 - Tunable White | | | | | | | | |
| MALTA 3 | MAT-30022 | 84 LED/m | 12 W | 376 lm | G [60°x111°] | TW (2700K - 6500K) | DALI | 2.1 kg/m |
| Without remote driver - Constant voltage (CV) 24 V - Stainless steel - IP20 | | | | | | | | |
| MALTA 2 | MAT-30011 | 120 LED/m | 9 W | 337 - 362 lm | G [60°x111°] | 3000K CRI80, 4000K CRI80, 5700K CRI80 | On/Off | 3.5 kg/m |
| Without remote driver - Constant voltage (CV) 24 V - Stainless steel - IP65 | | | | | | | | |
| MALTA 1 | MAT-30001 | 120 LED/m | 9 W | 303 - 325 lm | G [60°x111°] | 3000K CRI80, 4000K CRI80, 5700K CRI80 | On/Off | 3.5 kg/m |
| Without remote driver - Constant voltage (CV) 24 V - Stainless steel - IP65 - RGBW | | | | | | | | |
| MALTA 1 | MAT-30003 | 84 LED/m | 15 W | 365 - 373 lm | G [60°x111°] | RGBW30, RGBW40 | DMX, DMX/RDM | 3.5 kg/m |
| Without remote driver - Constant voltage (CV) 24 V - Stainless steel - IP65 - Tunable White | | | | | | | | |
| MALTA 1 | MAT-30002 | 84 LED/m | 12 W | 376 lm | G [60°x111°] | TW (2700K - 6500K) | DALI | 3.5 kg/m |



Accessory


| |  Connector for cap rail - Straight A30181 |  Connector for cap rail - Flush elbow 90° A30281 |  Connector for cap rail - Adjustable flush angle, 135° upwards A30381 |  Connector for cap rail - Adjustable flush angle, 135° downwards A30481 |  End cap for cap rail A30581 |  Wall bracket A30681 |  Driver (CV) - PWM - 100 W - IP65 - 24 V A33191-PW |
|-----------|---|--|---|---|--|--|--|
| MAT-30001 | • | • | • | • | • | • | • |
| MAT-30002 | • | • | • | • | • | • | • |
| MAT-30003 | • | • | • | • | • | • | • |
| MAT-30011 | • | • | • | • | • | • | • |
| MAT-30021 | • | • | • | • | • | • | • |
| MAT-30022 | • | • | • | • | • | • | • |
| MAT-30023 | • | • | • | • | • | • | • |
| MAT-30031 | • | • | • | • | • | • | • |

MALTA

| |  Driver (CV) - PWM - 150 W - IP65 - 24 V V A33291-PW |  Driver (CV) - PWM - 250 W - IP65 - 24 V V A33391-PW |  Driver (CV) - PWM - 320 W - IP65 - 24 V V A33491-PW |  Driver (CV) - On/Off - 36 W - IP67 - 24 V A34491-ND |  Driver (CV) - On/Off - 60 W - IP67 - 24 V A34591-ND |  Driver (CV) - On/Off - 100 W - IP67 - 24 V A34791-ND |  Driver (CV) - On/Off - 150 W - IP67 - 24 V A34891-ND |
|-----------|--|--|--|--|--|---|---|
| MAT-30001 | | | | . | . | . | . |
| MAT-30002 | . | . | . | | | | |
| MAT-30003 | . | . | . | | | | |
| MAT-30011 | | | | . | . | . | . |
| MAT-30021 | | | | . | . | . | . |
| MAT-30022 | . | . | . | | | | |
| MAT-30023 | . | . | . | | | | |
| MAT-30031 | | | | . | . | . | . |

| |  Driver (CV) - On/Off - 200 W - IP67 - 24 V A34991-ND |  Driver (CV) - On/Off - 350 W - IP67 - 24 V A35091-ND |  Constant voltage dimmer - 4 Channel A610291 |  DALI Control System Control-DALI |  DMX Control System Control-DMX |  DMX/RDM Control System Control-DMX- RDM |
|-----------|---|---|--|--|--|---|
| MAT-30001 | . | . | | . | | |
| MAT-30002 | | | | . | | |
| MAT-30003 | | | | . | . | . |
| MAT-30011 | . | . | | | | |
| MAT-30021 | . | . | | | | |
| MAT-30022 | | | | . | . | . |
| MAT-30023 | | | | . | . | . |
| MAT-30031 | . | . | | . | | |

MAT-30001, MAT-30021
MAT-30011, MAT-30031



MAT-30002, MAT-30003
MAT-30022, MAT-30023

