

ATLANTIC 10 (AA-30640-2-1)**Product description**

Shepherd's crook - Large - Straight shade - Dome top - IP65

**Luminaire Structure**

- Opal toughened glass diffuser


- Integral control gear

Product colour

01 - Black (RAL 9011) 02 - Dark Grey (RAL 7043) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)



06 - Bronze (RAL 6014)

Special finishes upon request

SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban



SW01 - Oak - Woodland SW02 - Walnut - Woodland SW03 - Pine - Woodland

ATLANTIC 10 (AA-30640-2-1)

Technical information

Material	Aluminium
Light source	24 LED
Power	40 W
Lumen	3429 - 4222 lm
Efficacy	86 - 106 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz
Optic	M, W, VW, EW, T2, T3, T4

Optic value	30°, 52°, 66°, 122°, 141°x51°, 141°x67°, 98°x69°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B1-U1-G1, B2-U1-G0, B3-U1-G0
ULR	0%
ULOR	0%
CIE flux code n°3	96, 99
Dimming type	On/Off, 1-10V, DALI
Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	13.5 kg

Operating temperature	-20 °C to 40 °C
Lens / Reflector / Optic	Opal toughened glass diffuser
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 90,000
Lifetime L80B10 (hours)	> 90,000
Lifetime L80B50 (hours)	> 90,000
Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

AA-30640-2-1

