

**ALDO 1** (ALD-30011) (Version 1)**Product description**

Without remote driver (CV) - Constant voltage (CV) 24 V - 28x40.7 mm - 1000 mm

**Luminaire Structure**

- Two cable entries for through wiring
- One cable gland supplied with 0.2 m of 3x1.0 sqmm outdoor cable
- Clear toughened glass
- Remote driver (not included)

**Optic**

EW

**Product colour**

05 - Matt Silver  
(RAL 9006)

**ALDO 1** (ALD-30011) (Version 1)

**Technical information**

<b>Material</b>	Aluminium	<b>Driver</b>	Constant voltage (CV)	<b>Product colours</b>	Matt Silver
<b>Light source</b>	48 LED	<b>Input voltage</b>	24 VDC	<b>Weight</b>	0.64 kg
<b>Power</b>	12 W	<b>Optic</b>	EW	<b>Operating temperature</b>	-20 °C to 40 °C
<b>Lumen</b>	712 - 762 lm	<b>Optic value</b>	90°	<b>Cable</b>	One cable gland supplied with 0.2 m of 3x1.0 sqmm outdoor cable
<b>Efficacy</b>	59 - 64 lm/W	<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80	<b>Through wiring</b>	Two cable entries for through wiring
<b>Driver option</b>	Remote driver (not included)	<b>Dimming type</b>	On/Off	<b>Lens / Reflector / Optic</b>	Clear toughened glass

**Accessories**



Driver (CV) - On/Off - 36 W - IP67 - 24 V  
**A34491-ND**



Driver (CV) - On/Off - 60 W - IP67 - 24 V  
**A34591-ND**



Driver (CV) - On/Off - 100 W - IP67 - 24 V  
**A34791-ND**



Driver (CV) - On/Off - 150 W - IP67 - 24 V  
**A34891-ND**



Driver (CV) - On/Off - 200 W - IP67 - 24 V  
**A34991-ND**



Driver (CV) - On/Off - 350 W - IP67 - 24 V  
**A35091-ND**