


ALDO 1 (ALD-30031) (Version 1)**Product description**

Without remote driver (CV) - Constant voltage (CV) 24 V - 28x43.5 mm - 1000 mm - RGBW dynamic programming - 32 addresses/channels

**Luminaire Structure**

- Two cable entries for through wiring
- One cable gland supplied with 0.2 m of 8x0.5 sqmm outdoor cable
- Clear toughened glass
- Remote driver (not included)

Optic

EW

Product colour

05 - Matt Silver
(RAL 9006)

ALDO 1 (ALD-30031) (Version 1)

Technical information

Material	Aluminium	Optic	EW	Product colours	Matt Silver
Light source	48 LED	Optic value	80°	Weight	0.72 kg
Power	12 W	CCT / CRI	RGBW40	Operating temperature	-20 °C to 40 °C
Lumen	255 lm	Bug	B0-U0-G0	Cable	One cable gland supplied with 0.2 m of 8x0.5 sqmm outdoor cable
Efficacy	21 lm/W	ULR	0%	Through wiring	Two cable entries for through wiring
Driver option	Remote driver (not included)	ULOR	0%	Lens / Reflector / Optic	Clear toughened glass
Driver	Constant voltage (CV)	CIE flux code n°3	100		
Input voltage	24 VDC	Dimming type	DMX, DMX/RDM		

Accessories



DMX Control System
Control-DMX



DMX/RDM Control System
Control-DMX-RDM



Driver (CV) - On/Off - 36 W - IP67 - 24 V
A34491-ND



Driver (CV) - On/Off - 60 W - IP67 - 24 V
A34591-ND



Driver (CV) - On/Off - 100 W - IP67 - 24 V
A34791-ND



Driver (CV) - On/Off - 150 W - IP67 - 24 V
A34891-ND



Driver (CV) - On/Off - 200 W - IP67 - 24 V
A34991-ND



Driver (CV) - On/Off - 350 W - IP67 - 24 V
A35091-ND