

**ALDO 2** (ALD-30051) (Version 1)**Product description**

---

Without remote driver (CV) - Constant voltage (CV) 24 V - 37x60.6 mm - 1000 mm

**Luminaire Structure**

---

- Two cable entries for through wiring
- One cable gland supplied with 0.2 m of 3x1.0 sqmm outdoor cable
- Clear toughened glass
- Remote driver (not included)

**ALDO 2** (ALD-30051) (Version 1)

**Technical information**

<b>Material</b>	Aluminium	<b>Driver</b>	Constant voltage (CV)	<b>Cable</b>	One cable gland supplied with 0.2 m of 3x1.0 sqmm outdoor cable
<b>Light source</b>	18 LED	<b>Input voltage</b>	24 VDC	<b>Through wiring</b>	Two cable entries for through wiring
<b>Power</b>	18 W	<b>Weight</b>	1.56 kg	<b>Lens / Reflector / Optic</b>	Clear toughened glass
<b>Driver option</b>	Remote driver (not included)	<b>Operating temperature</b>	-20 °C to 40 °C		

**Accessories**



Driver (CV) - On/Off - 36 W - IP67 - 24 V  
**A34491-ND**



Driver (CV) - On/Off - 60 W - IP67 - 24 V  
**A34591-ND**



Driver (CV) - On/Off - 100 W - IP67 - 24 V  
**A34791-ND**



Driver (CV) - On/Off - 150 W - IP67 - 24 V  
**A34891-ND**



Driver (CV) - On/Off - 200 W - IP67 - 24 V  
**A34991-ND**



Driver (CV) - On/Off - 350 W - IP67 - 24 V  
**A35091-ND**