



ALDO 2 (ALD-30061) (Version 1)**Product description**

Without remote driver (CV) - Constant voltage (CV) 24 V - 37x60.6 mm - 500 mm - RGBW

**Luminaire Structure**

- Two cable entries for through wiring
- One cable gland supplied with 0.2 m of 8x0.5 sqmm outdoor cable
- Clear toughened glass
- Remote driver (not included)

Optic**Product colour**

05 - Matt Silver
(RAL 9006)

ALDO 2 (ALD-30061) (Version 1)

Technical information

| | | | | | |
|----------------------|------------------------------|--------------------------|-------------------|---------------------------------|---|
| Material | Aluminium | Optic | M, W, E | Product colours | Matt Silver |
| Light source | 9 LED | Optic value | 30°, 45°, 25°x40° | Weight | 0.84 kg |
| Power | 9 W | CCT / CRI | RGBW40 | Operating temperature | -20 °C to 40 °C |
| Lumen | 342 - 345 lm | Bug | B1-U0-G0 | Cable | One cable gland supplied with 0.2 m of 8x0.5 sqmm outdoor cable |
| Efficacy | 38 lm/W | ULR | 0% | Through wiring | Two cable entries for through wiring |
| Driver option | Remote driver (not included) | ULOR | 0% | Lens / Reflector / Optic | Clear toughened glass |
| Driver | Constant voltage (CV) | CIE flux code n°3 | 100, 98, 99 | | |
| Input voltage | 24 VDC | Dimming type | DMX, DMX/RDM | | |

Accessories



DMX Control System
Control-DMX



DMX/RDM Control System
Control-DMX-RDM



Driver (CV) - On/Off - 36 W - IP67 - 24 V
A34491-ND



Driver (CV) - On/Off - 60 W - IP67 - 24 V
A34591-ND



Driver (CV) - On/Off - 100 W - IP67 - 24 V
A34791-ND



Driver (CV) - On/Off - 150 W - IP67 - 24 V
A34891-ND



Driver (CV) - On/Off - 200 W - IP67 - 24 V
A34991-ND



Driver (CV) - On/Off - 350 W - IP67 - 24 V
A35091-ND