



ALDO 2 (ALD-30101) (Version 1)**Product description**

Without remote driver (CV) - Constant voltage (CV) 24 V - 37x60.6 mm - 500 mm - RGBW

**Luminaire Structure**

- Two cable entries for through wiring
- One cable gland supplied with 0.2 m of 8x0.5 sqmm outdoor cable
- Clear toughened glass
- Remote driver (not included)

Optic**Product colour**

05 - Matt Silver
(RAL 9006)

ALDO 2 (ALD-30101) (Version 1)

Technical information

Material	Aluminium	Optic	M, W, E	Product colours	Matt Silver
Light source	9 LED	Optic value	30°, 45°, 25°x40°	Weight	0.85 kg
Power	12 W	CCT / CRI	RGBW40	Operating temperature	-20 °C to 40 °C
Lumen	512 - 519 lm	Bug	B1-U0-G0	Cable	One cable gland supplied with 0.2 m of 8x0.5 sqmm outdoor cable
Efficacy	43 lm/W	ULR	0%	Through wiring	Two cable entries for through wiring
Driver option	Remote driver (not included)	ULOR	0%	Lens / Reflector / Optic	Clear toughened glass
Driver	Constant voltage (CV)	CIE flux code n°3	100, 98, 99		
Input voltage	24 VDC	Dimming type	DMX, DMX/RDM		

Accessories



DMX Control System
Control-DMX



DMX/RDM Control System
Control-DMX-RDM



Driver (CV) - On/Off - 36 W - IP67 - 24 V
A34491-ND



Driver (CV) - On/Off - 60 W - IP67 - 24 V
A34591-ND



Driver (CV) - On/Off - 100 W - IP67 - 24 V
A34791-ND



Driver (CV) - On/Off - 150 W - IP67 - 24 V
A34891-ND



Driver (CV) - On/Off - 200 W - IP67 - 24 V
A34991-ND



Driver (CV) - On/Off - 350 W - IP67 - 24 V
A35091-ND