



**ALDO 3** (ALD-30191) (Version 1)**Product description**

Without remote driver (CV) - Constant voltage (CV) 24 V - 47x72 mm - 1000 mm - RGBW

**Luminaire Structure**

- Two cable entries for through wiring
- One cable gland supplied with 0.2 m of 8x0.5 sqmm outdoor cable
- Clear toughened glass
- Remote driver (not included)

**Optic****Product colour**

05 - Matt Silver  
(RAL 9006)

**ALDO 3** (ALD-30191) (Version 1)

**Technical information**

<b>Material</b>	Aluminium	<b>Optic</b>	M, W, E	<b>Product colours</b>	Matt Silver
<b>Light source</b>	24 LED	<b>Optic value</b>	30°, 45°, 25°x40°	<b>Weight</b>	2 kg
<b>Power</b>	55 W	<b>CCT / CRI</b>	RGBW40	<b>Operating temperature</b>	-20 °C to 40 °C
<b>Lumen</b>	1161 - 1412 lm	<b>Bug</b>	B1-U0-G0, B1-U1-G0	<b>Cable</b>	One cable gland supplied with 0.2 m of 8x0.5 sqmm outdoor cable
<b>Efficacy</b>	21 - 26 lm/W	<b>ULR</b>	0%	<b>Through wiring</b>	Two cable entries for through wiring
<b>Driver option</b>	Remote driver (not included)	<b>ULOR</b>	0%	<b>Lens / Reflector / Optic</b>	Clear toughened glass
<b>Driver</b>	Constant voltage (CV)	<b>CIE flux code n°3</b>	100, 98, 99		
<b>Input voltage</b>	24 VDC	<b>Dimming type</b>	DMX, DMX/RDM		

**Accessories**



DMX Control System  
**Control-DMX**



DMX/RDM Control System  
**Control-DMX-RDM**



Driver (CV) - On/Off - 36 W - IP67  
- 24 V  
**A34491-ND**



Driver (CV) - On/Off - 60 W - IP67  
- 24 V  
**A34591-ND**



Driver (CV) - On/Off - 100 W -  
IP67 - 24 V  
**A34791-ND**



Driver (CV) - On/Off - 150 W -  
IP67 - 24 V  
**A34891-ND**



Driver (CV) - On/Off - 200 W -  
IP67 - 24 V  
**A34991-ND**



Driver (CV) - On/Off - 350 W -  
IP67 - 24 V  
**A35091-ND**