


ALDO 4 (ALD-30201) (Version 1)**Product description**

Without remote driver (CV) - Constant voltage (CV) 24 V - 77x95 mm - 500 mm

**Luminaire Structure**

- Two cable entries for through wiring
- One cable gland supplied with 0.2 m of 3x1.0 sqmm outdoor cable
- Clear toughened glass
- Remote driver (not included)

Optic**Product colour**

ALDO 4 (ALD-30201) (Version 1)

Technical information

Material	Aluminium	Driver	Constant voltage (CV)	Product colours	Matt Silver
Light source	18 LED	Input voltage	24 VDC	Weight	1.43 kg
Power	36 W	Optic	N, M, W, E	Operating temperature	-20 °C to 40 °C
Lumen	2317 - 2510 lm	Optic value	12°, 30°, 45°, 15°x50°	Cable	One cable gland supplied with 0.2 m of 3x1.0 sqmm outdoor cable
Efficacy	64 - 70 lm/W	CCT / CRI	3000K CRI80, 4000K CRI80	Through wiring	Two cable entries for through wiring
Driver option	Remote driver (not included)	Dimming type	On/Off	Lens / Reflector / Optic	Clear toughened glass

Accessories



Driver (CV) - On/Off - 36 W - IP67 - 24 V
A34491-ND



Driver (CV) - On/Off - 60 W - IP67 - 24 V
A34591-ND



Driver (CV) - On/Off - 100 W - IP67 - 24 V
A34791-ND



Driver (CV) - On/Off - 150 W - IP67 - 24 V
A34891-ND



Driver (CV) - On/Off - 200 W - IP67 - 24 V
A34991-ND



Driver (CV) - On/Off - 350 W - IP67 - 24 V
A35091-ND