

ARIZONA 4 (AR-21041)



Product description

Top Ø160 mm - IK07



Luminaire Structure

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable

- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- High-efficiency optical reflector
- Clear acrylic PMMA diffuser


- Integral control gear

Optic




G

Product colour



Special finishes upon request




ARIZONA 4 (AR-21041)

Technical information

Material	Aluminium	Optic value	360°	Operating temperature	-20 °C to 40 °C
Light source	1 COB	CCT / CRI	3000K CRI80, 4000K CRI80	Cable	One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable
Power	28 W	Bug	B1-U3-G0	Through wiring	Single cable entry
Lumen	1707 - 1826 lm	ULR	4%	Lens / Reflector / Optic	High-efficiency optical reflector, Clear acrylic PMMA diffuser
Efficacy	61 - 65 lm/W	ULOR	4%	MacAdam Ellipse	3 SDCM
Driver option	Integral control gear	CIE flux code n°3	99	Lifetime L90B10 (hours)	> 61,000
Driver	Constant current (CC)	Dimming type	On/Off, 1-10V, DALI	Variants (On/Off, 1-10V)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Input voltage	220-240 V 50/60 Hz	Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland		
Optic	G	Weight	5.6 kg		

AR-21041



Accessories



DALI Control System
Control-DALI