

ARIZONA 6 (AR-21131)



Product description

Ø225 mm - Supplied with specific 3 m cylindrical, straight aluminium pole: APD130225-AR-21131 - 2 projectors - IP65 - IK06




microPrim™

Luminaire structure


- Die-cast aluminium housing
- Extruded aluminium column
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- High-efficiency optical reflector
- Clear acrylic PMMA diffuser
- Integral control gear
- Maximum wind load resistance is 140 km/h
- Surge protection 10kV
- For ARIZONA 8, the luminaire and the lighting pole with illuminated decorative graphic are controlled separately. Upon request, they can be controlled together by the same protocol, either DMX or DALI.

Optic




G

Product colour



Special finishes upon request




ARIZONA 6 (AR-21131)

Technical information

Material	Aluminium
Light source	3 COB
Power	74 W
Lumen	2967 - 6367 lm
Efficacy	78 - 92 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz
Optic	G
Optic value	60°x69°

CCT / CRI	2700K CRI80, 3000K CRI80, 4000K CRI80
Bug	B2-U3-G1
ULR	3%
ULOR	3%
CIE flux code n°3	98
Dimming type	On/Off, 1-10V, DALI
Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	48.0 kg
Operating temperature	-20 °C to 40 °C
EPA (m2)	1.080

Cable	One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable
Through wiring	Single cable entry
Lens / Reflector / Optic	High-efficiency optical reflector, Clear acrylic PMMA diffuser
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 50,700
Lifetime L80B10 (hours)	> 63,500
Lifetime L80B50 (hours)	> 63,500
Variants (On/Off, 1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)



ARIZONA 6 (AR-21131)**Accessory**



Circuit breaker box IP44
A21291



Root mount kit
A20791



DALI Control System
Control-DALI

Pole (required)



3 m - Cylindrical, straight
aluminium pole for ARIZONA
APD130225-AR-21131