

**ARDEN 4 (ARD-90043)**



**Product description**

Down - 875 mm - TW



**Luminaire Structure**

- Extruded aluminium bended profile with powder coating
- Stainless steel fasteners in grade 316
- Stainless steel, adjustable, suspension (1.5 m) complete with electrical wires in white for mounting
- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control

- Up and down light distribution options
- Passive thermal management
- Integral control gear
- Wireless control available through Bluetooth connection

- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

**Optic**




P

**Product colour**



01 - Black (RAL 9011)    03 - White (RAL 9003)    05 - Matt Silver (RAL 9006)

**Special finishes upon request**



SU01 - Concrete - Urban    SU02 - Softscape - Urban    SU03 - Stone - Urban    SU04 - Corten - Urban




SW01 - Oak - Woodland    SW02 - Walnut - Woodland    SW03 - Pine - Woodland

**ARDEN 4 (ARD-90043)**


**Technical information**

<b>Material</b>	Aluminium	<b>Input voltage</b>	220-240 V 50/60 Hz	<b>Operating temperature</b>	-20 °C to 40 °C
<b>Light source</b>	3024 LED	<b>Optic</b>	O, P	<b>Lens / Reflector / Optic</b>	PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control
<b>Power</b>	151 W	<b>Optic value</b>	108°, 93°	<b>MacAdam Ellipse</b>	3 SDCM
<b>Lumen</b>	20913 lm	<b>CCT / CRI</b>	TW (2700K - 6500K)	<b>Lifetime L90B10 (hours)</b>	> 23,000
<b>Efficacy</b>	138 lm/W	<b>Dimming type</b>	DALI	<b>Lifetime L80B10 (hours)</b>	> 45,000
<b>Driver option</b>	Integral control gear	<b>Product colours</b>	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland	<b>Lifetime L80B50 (hours)</b>	> 50,000
<b>Driver</b>	Constant current (CC)	<b>Weight</b>	12.1 kg	<b>Variants (DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)


ARD-90043



**Accessories**




Supply cable surface mounting box  
**A80981**



Wireless bluetooth converter  
**A90291**




Xpress wireless switch  
**A90591**




Decorative pattern - Type A for ARDEN 900 mm  
**A91821**

**ARDEN 4** (ARD-90043)



Decorative pattern - Type B for  
ARDEN 900 mm  
**A93221**



Decorative pattern - Type C for  
ARDEN for ARDEN 900 mm  
**A94621**



DALI Control System  
**Control-DALI**