

BORNHOLM 1 (BOH-60001)



Product description



Without remote box IP-rated - With remote driver /
recessing box - Constant current (CC) 350 mA



Luminaire Structure

- Stainless steel body in grade 316
- Single cable entry
- One cable gland supplied with 2 m of 2x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 316
- Durable silicone rubber gasket
- Clear toughened glass
- Remote driver (included)
- Remote box IP-rated is not included and is to be ordered separately for constant current (CC) products
- Recessing box in stainless steel 316 grade
- Luminaire must be submerged when operational
- Maximum depth 2 m
- Outdoor cable needs to be ordered with a specific length
- Maximum distance of the Remote DMX/RDM decoder is 8 m

Optic



Product colour




BORNHOLM 1 (BOH-60001)


Technical information

Material	Stainless Steel	Optic value	13°, 18°, 28°, 63°, 13°x42°	Operating temperature	-20 °C to 40 °C
Light source	1 LED	CCT / CRI	3000K CRI80, 4000K CRI80	Cable	One cable gland supplied with 2 m of 2x1.0 sqmm outdoor cable
Power	6 W	Bug	B0-U0-G0, B1-U0-G0	Through wiring	Single cable entry
Lumen	250 - 408 lm	ULR	0%	Lens / Reflector / Optic	Clear toughened glass
Efficacy	42 - 68 lm/W	ULOR	0%	MacAdam Ellipse	3 SDCM
Driver option	Remote driver (included)	CIE flux code n°3	100	Lifetime L90B10 (hours)	> 109,000
Driver	Constant current (CC)	Dimming type	On/Off, 1-10V	Lifetime L80B10 (hours)	> 109,000
Input voltage	350 mA, 12 VDC	Product colours	Stainless Steel	Lifetime L80B50 (hours)	> 109,000
Optic	N, M, W, VW, E	Weight	0.8 kg	Variants (On/Off, 1-10V)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

BOH-60001



Accessories



Honeycomb louvre
A52221



DALI Control System
Control-DALI



Remote box IP65
A80191