



BORNHOLM 1 (BOH-60002) (Version 1)**Product description**

Without remote driver - With remote DMX/RDM decoder - Constant voltage (CV) 24 V - RGBW

**Luminaire Structure**

- Stainless steel body in grade 316
- Single cable entry
- One cable gland supplied with 2 m of 5x0.75 sqmm outdoor cable
- Stainless steel fasteners in grade 316
- Durable silicone rubber gasket
- Clear toughened glass
- Remote driver (not included)
- Remote box IP-rated is not included and is to be ordered separately for constant current (CC) products
- Recessing box in stainless steel 316 grade
- Luminaire must be submerged when operational
- Maximum depth 2 m
- Outdoor cable needs to be ordered with a specific length
- Maximum distance of the Remote DMX/RDM decoder is 8 m

Optic**M****Product colour**


00 - Stainless Steel

BORNHOLM 1 (BOH-60002) (Version 1)


Technical information

Material	Stainless Steel	Optic value	34°	Operating temperature	-20 °C to 40 °C
Light source	1 LED	CCT / CRI	RGBW30, RGBW40	Cable	One cable gland supplied with 2 m of 5x0.75 sqmm outdoor cable
Power	4 W	Bug	B0-U0-G0	Through wiring	Single cable entry
Lumen	170 lm	ULR	0%	Lens / Reflector / Optic	Clear toughened glass
Efficacy	43 lm/W	ULOR	0%	MacAdam Ellipse	7 SDCM
Driver option	Remote driver (not included)	CIE flux code n°3	100	Lifetime L90B10 (hours)	> 15,000
Driver	Constant voltage (CV)	Dimming type	DMX, DMX/RDM	Lifetime L80B10 (hours)	> 31,000
Input voltage	24 VDC	Product colours	Stainless Steel	Lifetime L80B50 (hours)	> 34,000
Optic	M	Weight	0.8 kg		

BOH-60002



Accessories



Honeycomb louvre
A52221



DMX Control System
Control-DMX



DMX/RDM Control System
Control-DMX-RDM



Driver (CV) - On/Off - 36 W - IP67
- 24 V
A34491-ND



Driver (CV) - On/Off - 60 W - IP67
- 24 V
A34591-ND



Driver (CV) - On/Off - 100 W -
IP67 - 24 V
A34791-ND



Driver (CV) - On/Off - 150 W -
IP67 - 24 V
A34891-ND



Driver (CV) - On/Off - 200 W -
IP67 - 24 V
A34991-ND

BORNHOLM 1 (BOH-60002) (Version 1)

Driver (CV) - On/Off - 350 W -
IP67 - 24 V
A35091-ND
