


CAPSULE 4 (CA-30596-1MS)



Product description

With integrated motion sensor




Luminaire Structure

- Die-cast aluminium housing and frame
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring

- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Opal UV-stabilised polycarbonate diffuser

- Integral control gear

Optic



G

Product colour




01 - Black (RAL 9011) 02 - Dark Grey (RAL 7043) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)




06 - Bronze (RAL 6014)

Special finishes upon request



SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban



SW01 - Oak - Woodland



SW02 - Walnut - Woodland



SW03 - Pine - Woodland

CAPSULE 4 (CA-30596-1MS)



Technical information

Material	Aluminium
Light source	96 LED
Power	15 W
Lumen	1355 - 1427 lm
Efficacy	90 - 95 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz
Optic	G

Optic value	100°x151°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B0-U2-G1
ULR	15%
ULOR	15%
CIE flux code n°3	85
Dimming type	On/Off, 1-10V
Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	2.2 kg

Operating temperature	-20 °C to 50 °C
Through wiring	Two cable entries for through wiring
Lens / Reflector / Optic	Opal UV-stabilised polycarbonate diffuser
MacAdam Ellipse	3 SDCM
Lifetime L90B10 (hours)	> 37,000
Lifetime L80B10 (hours)	> 78,000
Lifetime L80B50 (hours)	> 86,000
Variants (On/Off, 1-10V)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

CA-30596-1MS



CAPSULE

- Motion sensor - Motion - 1-10 V**
 - Opal polycarbonate diffuser (30° beam) - 15 (max. 15m)
 - IP20
 - Sensor: 0.05m/0.05m/0.05m
 CA30596-MS(2) - 15m
 CA30596-MS(3) - 15m
 CA30596-MS(4) - 15m
 CA30596-MS(5) - 15m
 CA30596-MS(6) - 15m
- Motion sensor - Motion - On/Off**
 - Opal polycarbonate diffuser (30° beam) - 15 (max. 15m)
 - IP20
 - Sensor: 0.05m/0.05m/0.05m
 CA30596-MS(2) - 15m
 CA30596-MS(3) - 15m
 CA30596-MS(4) - 15m
 CA30596-MS(5) - 15m
 CA30596-MS(6) - 15m

Accessories



DALI Control System
Control-DALI



Remote controller for the motion sensor - 1-10V (A34191)
A34391