

CAPSULE 4 (CA-30597)**IP65****IK08****Product description**


TW

**Luminaire Structure**

- Die-cast aluminium housing and frame
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring

- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Opal UV-stabilised polycarbonate diffuser

- Integral control gear

Optic**G****Product colour**

01 - Black (RAL 9011)



02 - Dark Grey (RAL 7043)



03 - White (RAL 9003)



05 - Matt Silver (RAL 9006)



06 - Bronze (RAL 6014)

Special finishes upon request

SU01 - Concrete - Urban



SU02 - Softscape - Urban



SU03 - Stone - Urban



SU04 - Corten - Urban



SW01 - Oak - Woodland



SW02 - Walnut - Woodland



SW03 - Pine - Woodland

CAPSULE 4 (CA-30597)

Technical information

Material	Aluminium	Optic	G	Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Light source	192LED	Optic value	169°x108°		
Power	16 W	CCT / CRI	TW (2700K - 6500K)	Weight	2.2 kg
Lumen	1224 lm	Bug	B1-U3-G1	Operating temperature	-20 °C to 50 °C
Efficacy	77 lm/W	ULR	15.40%	Through wiring	Two cable entries for through wiring
Driver option	Integral control gear	ULOR	15.40%	Lens / Reflector / Optic	Opal UV-stabilised polycarbonate diffuser
Driver	Constant current (CC)	CIE flux code n°3	85	Variants (DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Input voltage	220-240 V 50/60 Hz	Dimming type	DALI		

CA-30597

