

**CAPSULE 5 (CA-30606-1MS)**



**Product description**

With integrated motion sensor



**Luminaire Structure**

- Die-cast aluminium housing and frame
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Opal UV-stabilised polycarbonate diffuser
- Integral control gear

**Optic**




G

**Product colour**



**Special finishes upon request**



**CAPSULE 5 (CA-30606-1MS)**



**Technical information**

<b>Material</b>	Aluminium
<b>Light source</b>	96 LED
<b>Power</b>	15 W
<b>Lumen</b>	670 - 705 lm
<b>Efficacy</b>	45 - 47 lm/W
<b>Driver option</b>	Integral control gear
<b>Driver</b>	Constant current (CC)
<b>Input voltage</b>	220-240 V 50/60 Hz
<b>Optic</b>	G

<b>Optic value</b>	96°x13°
<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80
<b>Bug</b>	B0-U2-G1
<b>ULR</b>	14%
<b>ULOR</b>	14%
<b>CIE flux code n°3</b>	85
<b>Dimming type</b>	On/Off, 1-10V
<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Weight</b>	2.2 kg

<b>Operating temperature</b>	-20 °C to 50 °C
<b>Through wiring</b>	Two cable entries for through wiring
<b>Lens / Reflector / Optic</b>	Opal UV-stabilised polycarbonate diffuser
<b>MacAdam Ellipse</b>	3 SDCM
<b>Lifetime L90B10 (hours)</b>	> 37,000
<b>Lifetime L80B10 (hours)</b>	> 78,000
<b>Lifetime L80B50 (hours)</b>	> 86,000
<b>Variants (On/Off, 1-10V)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

CA-30606-1MS



**CAPSULE**

- **Microcosm: Microcosm 1-10V**  
Adjustable sensor (11 models) - 15 minutes  
IP20 (standard)  
Sensor 0.85lx/1m²  
CA-30305\*1M1 (20 - 8.5lm)  
CA-30325\*1M1 (20 - 7.5lm)  
CA-30345\*1M1 (20 - 6.5lm)  
CA-30365\*1M1 (20 - 4.5lm)
- **Microcosm: Microcosm On/Off**  
Adjustable sensor (10 models) - 10 minutes  
IP20 (standard)  
Sensor 0.85lx/1m²  
CA-30315\*1M1 (20 - 5.5lm)  
CA-30335\*1M1 (20 - 4.5lm)  
CA-30355\*1M1 (20 - 3.5lm)  
CA-30375\*1M1 (20 - 2.5lm)

**Accessories**



DALI Control System  
**Control-DALI**



Remote controller for the motion sensor - 1-10V (A34191)  
**A34391**