


CEDAR 1 (CD-80001)**Product description**


118x238 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management

- Propriety lens design for high LOR
- Adjustable: Tilt 30°

- Remote driver is included


Optic**Product colour**

CEDAR 1 (CD-80001)

Technical information

Material	Aluminium	Optic value	19°, 31°, 48°	Operating temperature	-20 °C to 50 °C
Light source	2 x 5 LED	CCT / CRI	3000K CRI80, 4000K CRI80	Lens / Reflector / Optic	High-efficiency PMMA lens
Power	19 W	Bug	B1-U0-G0	MacAdam Ellipse	3 SDCM
Lumen	1660 - 1988 lm	ULR	0%	Lifetime L90B10 (hours)	> 120,000
Efficacy	87 - 105 lm/W	ULOR	0%	Lifetime L80B10 (hours)	> 120,000
Driver option	Remote driver (included)	CIE flux code n°3	100	Lifetime L80B50 (hours)	> 120,000
Driver	Constant current (CC)	Dimming type	On/Off, 1-10V, DALI, Trailing edge	Variants (On/Off, 1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Input voltage	500 mA, 15 VDC	Product colours	Glossy White, Glossy Black		
Optic	N, M, W	Weight	1.00 kg.		

CD-80001



Accessories



DALI Control System
Control-DALI