

**COLUMBUS 6 (CO-30166-1-2)**



**Product description**

Swept shade - Cone top



**Luminaire Structure**


- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Opal toughened glass diffuser
- Integral control gear
- Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible for COLUMBUS 6

**Optic**




G

**Product colour**



**Special finishes upon request**



**COLUMBUS 6 (CO-30166-1-2)**

**Technical information**

<b>Material</b>	Aluminium	<b>Optic</b>	G	<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland							
<b>Light source</b>	1 COB	<b>Optic value</b>	149°		<b>Weight</b>	9.0 kg						
<b>Power</b>	41 W	<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80			<b>Operating temperature</b>	-20 °C to 40 °C					
<b>Lumen</b>	2019 - 2044 lm	<b>Bug</b>	B1-U3-G1				<b>Through wiring</b>	Two cable entries for through wiring				
<b>Efficacy</b>	49 - 50 lm/W	<b>ULR</b>	22%					<b>Lens / Reflector / Optic</b>	Opal toughened glass diffuser			
<b>Driver option</b>	Integral control gear	<b>ULOR</b>	22%						<b>MacAdam Ellipse</b>	3 SDCM		
<b>Driver</b>	Constant current (CC)	<b>CIE flux code n°3</b>	86							<b>Lifetime L90B10 (hours)</b>	> 55,000	
<b>Input voltage</b>	220-240 V 50/60 Hz	<b>Dimming type</b>	On/Off, 1-10V, DALI								<b>Variants (1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

CO-30166-1-2

