

INFINITE FLEX 1 (FLE-30011-VB)



Product description

Diffused - 160 LED - 15W - IP67/IP68

Luminaire structure

- UV & flame resistant, chemical & salt stable PU
- Remote driver (not included)
- Needs to be ordered with a specific length and the type of cable entry required
- DC 24V input



Variant code	Lumen	Efficacy	CCT / CRI
FLE-30011-VB-G-9027-DA	210 lm/m	14 lm/W	2700K CRI90
FLE-30011-VB-G-9027-ND	210 lm/m	14 lm/W	2700K CRI90
FLE-30011-VB-G-9027-PWM	210 lm/m	14 lm/W	2700K CRI90
FLE-30011-VB-G-9030-DA	225 lm/m	15 lm/W	3000K CRI90
FLE-30011-VB-G-9030-ND	225 lm/m	15 lm/W	3000K CRI90
FLE-30011-VB-G-9030-PWM	225 lm/m	15 lm/W	3000K CRI90
FLE-30011-VB-G-9040-DA	240 lm/m	16 lm/W	4000K CRI90
FLE-30011-VB-G-9040-ND	240 lm/m	16 lm/W	4000K CRI90
FLE-30011-VB-G-9040-PWM	240 lm/m	16 lm/W	4000K CRI90

INFINITE FLEX 1 (FLE-30011-VB)

Technical information

Power	15 W/m	MacAdam Ellipse	3 SDCM	Cutting length	40 mm
Driver option	Remote driver (not included)	Optic	120°	Dimensions	Width: 16 mm x Height: 17 mm
Driver	Constant voltage (CV)	Lifetime L80B10 (hours)	> 0	Warranty	5 years
Input voltage	24 VDC	Maximum run per power feed	3 m using one feed	Minimum bend radius	150 mm
Operating temperature	-20°C ~ +50°C	LED pitch	8.5 mm	Bend direction	Vertical

FLE-30011-VB



INFINITE FLEX 1 (FLE-30011-VB)**Accessory**



Surface Mounted Clamp

A616891
