

**FRANKFURT 1 (FRN-80001)****Product description**

1212x32x52 mm

**Luminaire Structure**

- Die-cast aluminium end-caps and extruded aluminium profile with powder coating
- Cover polycarbonate diffuser
- Down light distribution
- Passive thermal management
- Integral control gear
- CRI 95
- With 3-phase universal adapter
- Suitable for emergency power

**Optic****G****Product colour**

03 - White (RAL 9003)

15 - Black (RAL 9005)

**FRANKFURT 1 (FRN-80001)**

**Technical information**

<b>Material</b>	Aluminium	<b>Driver option</b>	Integral control gear	<b>CCT / CRI</b>	3000K CRI95, 4000K CRI95
<b>Light source</b>	LED	<b>Driver</b>	Constant current (CC)	<b>Dimming type</b>	On/Off
<b>Power</b>	30 W	<b>Input voltage</b>	220-240 V 50/60 Hz	<b>Product colours</b>	Black, White
<b>Lumen</b>	3060 lm	<b>Optic</b>	G	<b>Weight</b>	0.76 kg
<b>Efficacy</b>	102 lm/W	<b>Optic value</b>	110°	<b>Operating temperature</b>	-20 °C to 40 °C

FRANKFURT 1  
FRN-80001

