



FUNEN 4 (FUN-50031) (Version 1)**Product description**

Without remote box IP-rated - With remote driver -
Constant current (CC) 1400 mA

**Luminaire Structure**

- Stainless steel body in grade 316
- Single cable entry
- One cable gland supplied with 2 m of 2x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 316
- Durable silicone rubber gasket
- Clear toughened glass
- Remote driver (included)
- Remote box IP-rated is not included and is to be ordered separately for constant current (CC) products
- Luminaire must be submerged when operational
- Maximum depth 2 m
- Outdoor cable needs to be ordered with a specific length
- Maximum distance of the Remote DMX/RDM decoder is 8 m

Optic**Product colour**


00 - Stainless Steel

FUNEN 4 (FUN-50031) (Version 1)


Technical information

Material	Stainless Steel	Optic value	10°, 16°, 32°, 71°, 11°x43°	Operating temperature	-20 °C to 40 °C
Light source	16 LED	CCT / CRI	3000K CRI80, 4000K CRI80	Cable	One cable gland supplied with 2 m of 2x1.0 sqmm outdoor cable
Power	39 W	Bug	B2-U0-G0, B3-U0-G0	Through wiring	Single cable entry
Lumen	3172 - 4416 lm	ULR	0%	Lens / Reflector / Optic	Clear toughened glass
Efficacy	81 - 113 lm/W	ULOR	0%	MacAdam Ellipse	3 SDCM
Driver option	Remote driver (included)	CIE flux code n°3	100	Lifetime L90B10 (hours)	> 120,000
Driver	Constant current (CC)	Dimming type	On/Off, 1-10V	Lifetime L80B10 (hours)	> 120,000
Input voltage	2670 mA, 12 VDC	Product colours	Stainless Steel	Lifetime L80B50 (hours)	> 120,000
Optic	N, M, W, VW, E	Weight	2.4 kg		

FUN-50031



Accessories



Honeycomb louvre
A52521



DALI Control System
Control-DALI



Remote box IP65
A61851