

## **GAVLE 5** (GAV-90144)








### **Product description**

Down (Optic) & Up (Optic 2nd) - 60x100 mm - 2500 mm - RGBW DMX



#### **Luminaire Structure**

- Extruded aluminium bended profile with powder coating
- Stainless steel fasteners in grade 316
- Stainless steel, adjustable, suspension (1.5 m) complete with electrical wires in white for mounting
- Opal PMMA diffuser (UGR <19) for glare control
- Up and down light distribution options
- Passive thermal management
- Integral control gear
- Remote driver is included for dimming type: 1-10V (-DI) for GAV-90001, GAV-90011, GAV-90021, GAV-90031, GAV-90041, GAV-90051, GAV-90061, GAV-90071, GAV-90101, GAV-90111, GAV-90121, GAV-90131, GAV-90141, GAV-90151, GAV-90161, GAV-90171
- Wireless control available through Bluetooth connection
- Daylight and occupancy sensor options

#### **Optic**



### **Product colour**



01 - Black (RAL 9011)



03 - White (RAL



05 - Matt Silver (RAL 9006)

#### Special finishes upon request



SU01 - Concrete



SU02 - Softscape -Urban



SU03 - Stone -Urban



SU04 - Corten

SW01 - Oak



SW02 - Walnut -

SW03 - Pine



# **GAVLE 5** (GAV-90144)


### **Technical information**

Material	Aluminium
Light source	2688 & 2688 LED
Power	296 W
Lumen	9252 lm
Efficacy	31 lm/W
Driver option	Remote driver (included)

Driver	Constant current (CC)
Input voltage	200 mA,
Optic	0
Optic value	102°
CCT / CRI	RGBW30, RGBW40
Dimming type	DMX, DMX/RDM

Product colours	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	24.5 kg
Operating temperature	-20 °C to 40 °C
Variants (DMX/RDM)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (70)

#### GAV-90144



# Accessories





