

GAVLE 6 (GAV-90204)**Product description**




Down - 100x90 mm - 500 mm - RGBW DMX

**Luminaire Structure**

- Remote driver (included)

Optic

0


Product colour01 - Black (RAL
9011)03 - White (RAL
9003)05 - Matt Silver
(RAL 9006)**Special finishes upon request**SU01 - Concrete -
UrbanSU02 - Softscape -
UrbanSU03 - Stone -
UrbanSU04 - Corten -
UrbanSW01 - Oak -
WoodlandSW02 - Walnut -
WoodlandSW03 - Pine -
Woodland

GAVLE 6 (GAV-90204)

Technical information

| | | | | | |
|----------------------|--------------------------|----------------------|-----------------------|------------------------------|---|
| Material | Aluminium | Driver | Constant current (CC) | Product colours | Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland |
| Light source | 1152 LED | Input voltage | 250 mA, | Weight | 4.3 kg |
| Power | 41 W | Optic | 0 | Operating temperature | -20 °C to 40 °C |
| Lumen | 1444 lm | Optic value | 102° | Variants (DMX/RDM) | Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0) |
| Efficacy | 35 lm/W | CCT / CRI | RGBW30, RGBW40 | | |
| Driver option | Remote driver (included) | Dimming type | DMX, DMX/RDM | | |

Gavle 500



Accessories



Recessing box
A61051



DMX Control System
Control-DMX



DMX/RDM Control System
Control-DMX-RDM