

HARRIER 1 (HA-60036-A)



Product description

Integral control gear - With recessing box - Round - Aluminium frame



Luminaire Structure

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- 6 mm thick front ring in grade 316 stainless steel or aluminium
- Single cable entry, through wiring upon request

- One cable gland supplied with 1 m of 3x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear or frosted toughened glass

- Integral control gear
- Recessing box in high-density polyethylene is included
- Suitable for walk-over with a maximum load of 200 kg

Optic



C F

Product colour




01 - Black (RAL 9011) 02 - Dark Grey (RAL 7043) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)



06 - Bronze (RAL 6014)


Special finishes upon request




SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban



SW01 - Oak - Woodland



SW02 - Walnut - Woodland




SW03 - Pine - Woodland

HARRIER 1 (HA-60036-A)

Technical information

Material	Aluminium	Optic value	90°, 78°	Cable	One cable gland supplied with 1 m of 3x1.0 sqmm outdoor cable
Light source	12 LED	CCT / CRI	3000K CRI80, 4000K CRI80	Through wiring	Single cable entry, through wiring upon request
Power	6 W	Bug	B0-U3-G0	Lens / Reflector / Optic	Clear or frosted toughened glass
Lumen	163 - 291 lm	ULR	100%	MacAdam Ellipse	3 SDCM
Efficacy	27 - 49 lm/W	ULOR	100%	Lifetime L90B10 (hours)	> 23,000
Driver option	Integral control gear	Dimming type	On/Off	Lifetime L80B10 (hours)	> 45,000
Driver	Constant current (CC)	Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland	Lifetime L80B50 (hours)	> 50,000
Input voltage	220-240 V 50/60 Hz			Variants (On/Off)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (ZO)
Optic	C, F	Weight	0.5 kg		
		Operating temperature	-20 °C to 50 °C		

HA-60036-A



Accessories



Connector IP68 3 Pin Power
A62591



Connector IP68 5 Pin Power +
Signal
A613191