



HAYS 3 (HY-80041)**Product description**

Ø138 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Aluminium reflector with white powder coating
- Adjustable: Tilt 30°
- Remote driver is included


Optic**Product colour**

HAYS 3 (HY-80041)

Technical information

Material	Aluminium	Input voltage	500 mA, 36 VDC	Operating temperature	-20 °C to 40 °C
Light source	12 LED	Optic	N, M, W	MacAdam Ellipse	3 SDCM
Power	20 W	Optic value	23°, 30°, 35°	Lifetime L90B10 (hours)	> 120,000
Lumen	883 - 1164 lm	CCT / CRI	3000K CRI80, 4000K CRI80	Lifetime L80B10 (hours)	> 120,000
Efficacy	44 - 58 lm/W	Dimming type	On/Off, 1-10V, DALI	Lifetime L80B50 (hours)	> 120,000
Driver option	Remote driver (included)	Product colours	Glossy White, Glossy Black	Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Driver	Constant current (CC)	Weight	1.06 kg.		

HY-80041



Accessories



DALI Control System
Control-DALI