

LINE 2 (ITRB09XXXX1220)



Product description

9 W/m - Maximum run per feed 12 m



Luminaire Structure

- 24V DC
- CRI 90
- 3 SDCM
- Dimmable by PWM signal
- L80 B10: 50,000 hours
- IP20 and IP65 options
- 5 years warranty
- 3M adhesive backing. A LIGMAN approved aluminium profile for thermal management is required
- Sold in 5-metre length
- Remote driver is not included

| Variant code | Lumen | Efficacy | CCT / CRI |
|----------------|----------|----------|-------------|
| ITRB0930001220 | 801 lm/m | 92 lm/W | 3000K CRI90 |
| ITRB0940001220 | 827 lm/m | 95 lm/W | 4000K CRI90 |
| ITRB0950001220 | 835 lm/m | 96 lm/W | 5000K CRI90 |

LINE 2 (ITRB09XXXX1220)

Technical information

| | | | | | |
|------------------------------|------------------------------|-----------------------------------|----------|-------------------|---|
| Power | 8.7 W/m | MacAdam Ellipse | 3 SDCM | Control | Constant voltage dimmer (1 Channel) |
| Driver option | Remote driver (not included) | Optic | 120° | Dimensions | Width: 10 mm |
| Driver | Constant voltage (CV) | Lifetime L80B10 (hours) | > 50,000 | Warranty | 5 years |
| Input voltage | 24V DC | Maximum run per power feed | 12 m | Notes | Colour variance +/- 200K. Electrical & optical data variance +/- 10%. |
| Input current | 362 mA/m | LED pitch | 8.3 mm | | |
| Operating temperature | -20°C ~ +60°C | Cutting length | 50 mm | | |

Accessories



Driver (CV) - On/Off - 60 W - IP67 - 24 V
A34591-ND



Driver (CV) - On/Off - 100 W - IP67 - 24 V
A34791-ND



Driver (CV) - On/Off - 150 W - IP67 - 24 V
A34891-ND