

KIOS 8 (KI-60801)



Product description

With recessing box / driver - Flat frame - Adjustable:
Tilt 5° or 10° (2 step)



Luminaire Structure

- | | | |
|---|---|--|
| <ul style="list-style-type: none"> - Die-cast aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - 5.5 mm thick front ring in grade 316 stainless steel - Single cable entry, through wiring upon request - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) | <ul style="list-style-type: none"> - Durable silicone rubber gasket - Clear toughened glass - High-efficiency PMMA lens - Integral control gear - Recessing box in high-density polyethylene is included | <ul style="list-style-type: none"> - Suitable for drive-over with a maximum load of 2000 kg - Vehicles with pneumatic tires can drive over the luminaire but the speed must not exceed 50 km/h - Load is transferred by the housing to the foundation - The distance between the floodlight and the illuminated surface should be at least 0.5 m |
|---|---|--|

Optic



Product colour





KIOS 8 (KI-60801)

Technical information

Material	Stainless Steel	Optic value	16°, 28°, 40°	Through wiring	Single cable entry, through wiring upon request
Light source	18 LED	CCT / CRI	3000K CRI80, 4000K CRI80	Lens / Reflector / Optic	Clear toughened glass, High-efficiency PMMA lens
Power	30 W	Bug	B0-U5-G0	MacAdam Ellipse	3 SDCM
Lumen	2872 - 3160 lm	ULR	100%	Lifetime L90B10 (hours)	> 120,000
Efficacy	96 - 105 lm/W	ULOR	100%	Lifetime L80B10 (hours)	> 120,000
Driver option	Integral control gear	Dimming type	On/Off, 1-10V, DALI	Lifetime L80B50 (hours)	> 120,000
Driver	Constant current (CC)	Product colours	Stainless Steel	Variants (1-10V)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Input voltage	220-240 V 50/60 Hz	Weight	8.7 kg		
Optic	N, M, W	Operating temperature	-20 °C to 40 °C		

KI-60801



Accessories



Anti slip glass
A61612



Connector IP68 3 Pin Power
A62591



DALI Control System
Control-DALI



Connector IP68 5 Pin Power +
Signal
A613191