

LIGHTALK 14 (LA-30033) (Version 1)



Product description

Without remote driver - Constant voltage (CV) 24 V - 610 mm - Class III




Luminaire Structure

- Die-cast aluminium end-caps
- Extruded aluminium housing and sheet aluminium front frame
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring


- Four IP67 connectors supplied with 2x0.2 m of 3x1.0 sqmm outdoor cable and 2x0.2 m of 2x0.5 sqmm outdoor shielded cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass

- Remote driver (not included)
- Remote box IP-rated is not included and is to be ordered separately for constant current (CC) products
- 24 VDC input, DMX/RDM address with stable signal


Optic



Product colour



Special finishes upon request




LIGHTALK 14 (LA-30033) (Version 1)

Technical information

Material	Aluminium	Optic	VN, N, M, W, E	Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Light source	18 LED	Optic value	13°, 15°, 27°, 44°, 22° x 36°	Weight	2.6 kg
Power	25 W	CCT / CRI	3000K CRI80, 4000K CRI80	Operating temperature	-20 °C to 40 °C
Lumen	2202 - 2760 lm	Bug	B2-U1-G0, B3-U1-G0	Cable	Four IP67 connectors supplied with 2x0.2 m of 3x1.0 sqmm outdoor cable and 2x0.2 m of 2x0.5 sqmm outdoor shielded cable
Efficacy	88 - 110 lm/W	ULR	0%	Through wiring	Two cable entries for through wiring
Driver option	Remote driver (not included)	ULOR	0%	Lens / Reflector / Optic	Clear toughened glass
Driver	Constant voltage (CV)	CIE flux code n°3	100		
Input voltage	24 VDC	Dimming type	On/Off		

LA-30033



Accessories



Cable - Connector IP67 Female 2 Pin Power - 1000 mm
A65491-001

Cable - Connector IP67 Female 2 Pin Power - 5000 mm
A65491-005

Cable - Connector IP67 Female + Male 2 Pin Power - 1000 mm
A65591-001

Cable - Connector IP67 Female + Male 2 Pin Power - 5000 mm
A65591-005

LIGHTALK 14 (LA-30033) (Version 1)

Connector IP67 Female 2 Pin
Power
A68191



Connector IP67 Male 2 Pin
Power
A68291



End cap - Connector IP67
Female 2 Pin and 3 Pin Power
A67991



End cap - Connector IP67 Male 2
Pin and 3 Pin Power
A68091



Driver (CV) - On/Off - 36 W - IP67
- 24 V
A34491-ND



Driver (CV) - On/Off - 60 W - IP67
- 24 V
A34591-ND



Driver (CV) - On/Off - 100 W -
IP67 - 24 V
A34791-ND



Driver (CV) - On/Off - 150 W -
IP67 - 24 V
A34891-ND



Driver (CV) - On/Off - 200 W -
IP67 - 24 V
A34991-ND



Driver (CV) - On/Off - 350 W -
IP67 - 24 V
A35091-ND



75 mm extend arm mounting
A30891



150 mm extend arm mounting
A30991



300 mm extend arm mounting
A31091



450 mm extend arm mounting
A31191