

LIGHTALK 10 (LA-40013)







IK10

Product description

Without recessing box - Integral control gear - 655 mm

- Class I - RGBW

Luminaire Structure

- Die-cast aluminium end-caps
- Extruded aluminium housing and sheet aluminium front frame
- Pre-treated before powder coating ensuring high corrosion resistance
- Stainless steel frame on request
- Two cable entries for through wiring
- Four IP67 connectors supplied with 2x0.2 m of 3x1.0 sqmm outdoor cable and 2x0.2 m of 2x0.5 sgmm outdoor shielded cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- Integral control gear

- Recessing box is not included
- 24 VDC input, DMX/RDM address with stable signal

Optic





Product colour



06 - Bronze (RAL

02 - Dark Grey (RAL 7043)







05 - Matt Silver

SU01 - Concrete Urban







Special finishes upon request



SU04 - Corten -Urban

SW01 - Oak -Woodland

SW02 - Walnut -

SW03 - Pine

We reserve the right to make technical and design changes.



LIGHTALK 10 (LA-40013)


Technical information


Material	Aluminium
Light source	20 LED
Power	33 W
Lumen	1592 - 1916 lm
Efficacy	48 - 58 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz

Optic	VN, N, M, W, E
Optic value	10°, 13°, 24°, 43°, 16° x35°
CCT / CRI	RGBW30, RGBW40
Bug	B2-U1-G0
ULR	0%
ULOR	0%
CIE flux code nº3	100
Dimming type	DMX, DMX/RDM

Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
4.3 kg
-20 °C to 40 °C
Four IP67 connectors supplied with 2x0.2 m of 3x1.0 sqmm outdoor cable and 2x0.2 m of 2x0.5 sqmm outdoor shielded cable
Two cable entries for through wiring
Clear toughened glass
Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

LA-40013





Accessories







We reserve the right to make technical and design changes.