

LIGHTALK 13 (LA-95033) (Version 1)



Product description

Without remote driver - Constant voltage (CV) 24 V - 1205 mm - Class III




Luminaire Structure

- Die-cast aluminium end-caps
- Extruded aluminium housing and frame
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Two IP67 connectors supplied with 2x0.3 m of 2x1.0 sqmm outdoor cable


- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- Remote driver (not included)
- Remote box IP-rated is not included and is to be ordered separately for constant current (CC) products

- Stainless steel suspension kit in grade 304
- Suspension height is fully adjustable


Optic



Product colour



Special finishes upon request




LIGHTALK 13 (LA-95033) (Version 1)





Technical information

Material	Aluminium	Optic	VN, N, M, W, E	Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Light source	36 LED	Optic value	13°, 15°, 25°, 43°, 22° x 36°	Weight	4.0 kg
Power	51 W	CCT / CRI	3000K CRI80, 4000K CRI80	Operating temperature	-20 °C to 40 °C
Lumen	3871 - 4975 lm	Bug	B2-U1-G0, B3-U1-G0	Cable	Two IP67 connectors supplied with 2x0.3 m of 2x1.0 sqmm outdoor cable
Efficacy	76 - 98 lm/W	ULR	0%	Through wiring	Two cable entries for through wiring
Driver option	Remote driver (not included)	ULOR	0%	Lens / Reflector / Optic	Clear toughened glass
Driver	Constant voltage (CV)	CIE flux code n°3	100		
Input voltage	24 VDC	Dimming type	On/Off		

LA-95033



Accessories

			
Cable - Connector IP67 Female 2 Pin Power - 1000 mm A65491-001	Cable - Connector IP67 Female 2 Pin Power - 5000 mm A65491-005	Cable - Connector IP67 Female + Male 2 Pin Power - 1000 mm A65591-001	Cable - Connector IP67 Female + Male 2 Pin Power - 5000 mm A65591-005

LIGHTALK 13 (LA-95033) (Version 1)

Connector IP67 Female 2 Pin
Power
A68191



Connector IP67 Male 2 Pin
Power
A68291



Driver (CV) - On/Off - 36 W - IP67
- 24 V
A34491-ND



Driver (CV) - On/Off - 60 W - IP67
- 24 V
A34591-ND



Driver (CV) - On/Off - 100 W -
IP67 - 24 V
A34791-ND



Driver (CV) - On/Off - 200 W -
IP67 - 24 V
A34991-ND



Driver (CV) - On/Off - 350 W -
IP67 - 24 V
A35091-ND
