


**LBX 2 (LB-40438) (Version 2)**



**Product description**

Without remote driver - With recessing box - Constant current (CC) 500 mA - Class III



**Luminaire Structure**

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- One cable gland supplied with 0.3 m of 3x0.5 sqmm outdoor cable

- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- Remote driver (not included)


- Recessing box is included

**Optic**




G

**Product colour**



**Special finishes upon request**




**LBX 2 (LB-40438) (Version 2)**

**Technical information**

<b>Material</b>	Aluminium	<b>Optic value</b>	34° x 68°	<b>Operating temperature</b>	-20 °C to 40 °C
<b>Light source</b>	1 LED	<b>CCT / CRI</b>	3000K CRI80, 4000K CRI80	<b>Cable</b>	One cable gland supplied with 0.3 m of 3x0.5 sqmm outdoor cable
<b>Power</b>	2 W	<b>Bug</b>	B0-U1-G0	<b>Through wiring</b>	Single cable entry
<b>Lumen</b>	39 lm	<b>ULR</b>	4%	<b>Lens / Reflector / Optic</b>	Clear toughened glass
<b>Efficacy</b>	20 lm/W	<b>ULOR</b>	4%	<b>MacAdam Ellipse</b>	3 SDCM
<b>Driver option</b>	Remote driver (not included)	<b>CIE flux code n°3</b>	97	<b>Lifetime L90B10 (hours)</b>	> 120,000
<b>Driver</b>	Constant current (CC)	<b>Dimming type</b>	On/Off, 1-10V, DALI	<b>Lifetime L80B10 (hours)</b>	> 120,000
<b>Input voltage</b>	500 mA, 3 VDC	<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland	<b>Lifetime L80B50 (hours)</b>	> 120,000
<b>Optic</b>	G			<b>Variants (On/Off, 1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)

**LB-40438**



**Accessories**



Driver (CC) - DALI - 20 W - IP20 - 700 mA max  
**A32691-DA**



Driver (CC)- 1-10V - 20 W - IP20 - 700 mA max  
**A32691-DI**



Driver (CC) - On/Off - 20 W - IP20 - 700 mA max  
**A32691-ND**



Remote box IP65  
**A80191**