

MALMO 2 (MAL-80101)



Product description

Down - Trimless - 305 mm



Luminaire Structure

- Extruded aluminium bended profile with powder coating
- Stainless steel fasteners in grade 316
- Stainless steel brackets and screws for mounting
- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control

- Up and down light distribution options
- Passive thermal management
- Integral control gear
- Wireless control available through Bluetooth connection

- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

Optic



P

Product colour



01 - Black (RAL 9011) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)

Special finishes upon request



SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban




SW01 - Oak - Woodland SW02 - Walnut - Woodland SW03 - Pine - Woodland

MALMO 2 (MAL-80101)


Technical information

Material	Aluminium	Optic	O, P	Product colours	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Light source	168 LED	Optic value	107°, 94°		
Power	15 W	CCT / CRI	3000K CRI80, 4000K CRI80	Weight	1.6 kg
Lumen	1428 - 1715 lm	Bug	B1-U0-G0, B1-U0-G1		
Efficacy	68 - 82 lm/W	ULR	0%	Operating temperature	-20 °C to 40 °C
Driver option	Integral control gear	ULOR	0%		
Driver	Constant current (CC)	CIE flux code n°3	97, 98	MacAdam Ellipse	3 SDCM
Input voltage	220-240 V 50/60 Hz	Dimming type	On/Off, 1-10V, DALI		
				Variants (On/Off, 1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)


MAL-80101




Accessories




Decorative pattern - Type A for MALMO 300 mm
A90821



Decorative pattern - Type C for MALMO 300 mm
A93621



Decorative pattern - Type B for MALMO 300 mm
A92221



Wireless bluetooth converter
A90291

MALMO 2 (MAL-80101)



Xpress wireless switch
A90591



DALI Control System
Control-DALI