

MALMO 2 (MAL-80132)



Product description

Down - Trimless - 585 mm



Luminaire Structure

- Extruded aluminium bended profile with powder coating
- Stainless steel fasteners in grade 316
- Stainless steel brackets and screws for mounting
- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control

- Up and down light distribution options
- Passive thermal management
- Integral control gear
- Wireless control available through Bluetooth connection

- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

Optic



P

Product colour



01 - Black (RAL 9011) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)

Special finishes upon request



SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban



SW01 - Oak - Woodland SW02 - Walnut - Woodland SW03 - Pine - Woodland

MALMO 2 (MAL-80132)


Technical information

Material	Aluminium
Light source	624 LED
Power	77 W
Lumen	8265 - 9770 lm
Efficacy	106 - 125 lm/W
Driver option	Remote driver (included)
Driver	Constant current (CC)


Input voltage	220-240 V 50/60 Hz
Optic	O, P
Optic value	107°, 94°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B3-U0-G1
ULR	0%
ULOR	0%

CIE flux code n°3	96, 98
Dimming type	On/Off, 1-10V, DALI
Product colours	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	7.2 kg
Operating temperature	-20 °C to 40 °C
Variants (On/Off, 1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)


MAL-80132




Accessories




Decorative pattern - Type A for MALMO 600 mm
A91121



Decorative pattern - Type B for MALMO 600 mm
A92521



Decorative pattern - Type C for MALMO 600 mm
A93921



Wireless bluetooth converter
A90291



Xpress wireless switch
A90591



Emergency module - 250V - BASIC
EM250V-BA



Emergency module - 250V - PRO-DALI
EM250V-DA



Emergency module - 250V - SELF-TEST
EM250V-ST

MALMO 2 (MAL-80132)



DALI Control System
Control-DALI