

MALMO 3 (MAL-80242)



Product description

Down - 980 mm



Luminaire Structure

- Extruded aluminium bended circular profile with powder coating
- Multiple diameters available
- Stainless steel fasteners in grade 316
- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control

- Down light distribution only
- Passive thermal management
- Integral control gear
- Remote driver is included if dimming options require

- Wireless control available through Bluetooth connection
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

Optic



P

Product colour



01 - Black (RAL 9011) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)

Special finishes upon request



SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban




SW01 - Oak - Woodland SW02 - Walnut - Woodland SW03 - Pine - Woodland

MALMO 3 (MAL-80242)


Technical information

Material	Aluminium	Input voltage	220-240 V 50/60 Hz	CIE flux code n°3	96, 97
Light source	1872 LED	Optic	O, P	Dimming type	On/Off, 1-10V, DALI
Power	157 W	Optic value	107°, 94°	Product colours	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Lumen	18547 - 21948 lm	CCT / CRI	3000K CRI80, 4000K CRI80		Weight
Efficacy	79 - 94 lm/W	Bug	B4-U0-G2	Operating temperature	-20 °C to 40 °C
Driver option	Remote driver (included)	ULR	0%	Variants (On/Off, 1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Driver	Constant current (CC)	ULOR	0%		


MAL-80242




Accessories




Decorative pattern - Type A for MALMO 1000 mm
A91221



Decorative pattern - Type B for MALMO 1000 mm
A92621



Decorative pattern - Type C for MALMO 1000 mm
A94021



Wireless bluetooth converter
A90291

MALMO 3 (MAL-80242)

Xpress wireless switch
A90591



Emergency module - 250V -
BASIC
EM250V-BA



Emergency module - 250V -
PRO-DALI
EM250V-DA



Emergency module - 250V -
SELF-TEST
EM250V-ST



DALI Control System
Control-DALI