

MALMO 4 (MAL-90014)



Product description

Down - 390 mm - RGBW



Luminaire Structure

- Extruded aluminium bended profile with powder coating
- Stainless steel fasteners in grade 316
- Stainless steel, adjustable, suspension (1.5 m) complete with electrical wires in white for mounting
- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control

- Up and down light distribution options
- Passive thermal management
- Integral control gear
- Wireless control available through Bluetooth connection

- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

Optic




P

Product colour



01 - Black (RAL 9011) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)

Special finishes upon request



SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban




SW01 - Oak - Woodland SW02 - Walnut - Woodland SW03 - Pine - Woodland

MALMO 4 (MAL-90014)


Technical information

Material	Aluminium	Driver	Constant current (CC)	Product colours	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Light source	1104 LED	Input voltage	220-240 V 50/60 Hz	Weight	2.6 kg
Power	55 W	Optic	O, P	Operating temperature	-20 °C to 40 °C
Lumen	1494 lm	Optic value	107°, 94°	Variants (Bluetooth)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Efficacy	38 lm/W	CCT / CRI	RGBW40		
Driver option	Remote driver (included)	Dimming type	Bluetooth		

MAL-90014




Accessories




Supply cable surface mounting box
A80981




Xpress wireless switch
A90591



Decorative pattern - Type A for MALMO 300 mm
A90821



Decorative pattern - Type B for MALMO 300 mm
A92221



Decorative pattern - Type C for MALMO 300 mm
A93621



Recessing box
A61051



DALI Control System
Control-DALI