

MARVEL 3 (MAV-20002)



Product description


Ø76 mm - Supplied with specific 2.5 m cylindrical, straight aluminium pole: APD125076-MARVEL - Optic 90°x90°




Luminaire Structure

- Die-cast aluminium housing
- Extruded aluminium column
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- High-efficiency PMMA lens
- Clear toughened glass
- Integral control gear

Product colour



Special finishes upon request




MARVEL 3 (MAV-20002)

Technical information

Material	Aluminium
Light source	12 LED
Power	19 W
Lumen	1319 - 1680 lm
Efficacy	69 - 88 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)

Input voltage	220-240 V 50/60 Hz
Optic value	90°x90°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B1-U2-G1
ULR	1.24%
ULOR	1.24%
CIE flux code n°3	98

Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
Weight	8.0 kg
Operating temperature	-20 °C to 40 °C
Cable	One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable
Through wiring	Single cable entry
Lens / Reflector / Optic	High-efficiency PMMA lens, Clear toughened glass
VARIANTS	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)



Accessories



Root mount kit
A24391