


MATRIX 7 (MT-31398)



Product description

Down (Optic) & Up (Optic 2nd) with 1 special light effect



Luminaire Structure

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)


- Durable silicone rubber gasket
- Clear toughened glass
- High-efficiency PMMA lens
- High-efficiency optical reflector

- Integral control gear
- Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible
- MATRIX luminaires with uplight and colder than 3000K CCT do not meet the IDA certification requirements


Optic



Product colour



Special finishes upon request




MATRIX 7 (MT-31398)

Technical information

Material	Aluminium	Optic	N, M, W, VW	Operating temperature	-20 °C to 40 °C
Light source	1 COB & 1 LED	Optic value	20°, 25°, 36°, 74°	Through wiring	Single cable entry
Power	19 W	Optic (2nd)	ML	Lens / Reflector / Optic	Clear toughened glass, High-efficiency PMMA lens, High-efficiency optical reflector
Lumen	1191 - 1247 lm	Optic (2nd) value	85°	MacAdam Ellipse	3 SDCM
Efficacy	63 - 66 lm/W	CCT / CRI	3000K CRI80, 4000K CRI80	Lifetime L90B10 (hours)	> 55,000
Driver option	Integral control gear	Dimming type	On/Off, 1-10V, DALI	Variants (On/Off, 1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Driver	Constant current (CC)	Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland		
Input voltage	220-240 V 50/60 Hz	Weight	2.3 kg		

MT-31398



Accessories



Surface mounting box for easy cabling (MATRIX 7)
SCE-MATRIX-7



DALI Control System
Control-DALI