


MARYS 3 (MY-80031)**Product description**

Ø107 mm

**Luminaire Structure**

- Die-cast aluminium housing with powder coating
- Die-cast aluminium heat sink with excellent thermal management
- Propriety lens design for high LOR
- Remote driver is included


Optic**Product colour**

MARYS 3 (MY-80031)

Technical information

| | | | | | |
|----------------------|--------------------------|----------------------|------------------------------------|-------------------------------|---|
| Material | Aluminium | Driver | Constant current (CC) | Product colours | Glossy White, Glossy Black |
| Light source | 9 LED | Input voltage | 500 mA, 27 VDC | Weight | 0.76 kg. |
| Power | 15 W | Optic | N, M, W | Operating temperature | -20 °C to 40 °C |
| Lumen | 1413 - 1672 lm | Optic value | 14°, 25°, 39° | Variants (1-10V, DALI) | Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0) |
| Efficacy | 94 - 111 lm/W | CCT / CRI | 3000K CRI80, 4000K CRI80 | | |
| Driver option | Remote driver (included) | Dimming type | On/Off, 1-10V, DALI, Trailing edge | | |

MY-80031



Accessories



DALI Control System
Control-DALI