


**NYBRO 8 (NYB-30226)**



**Product description**

Down - 60x80 mm - 1178 mm - RGBW




**Luminaire Structure**

- Die-cast aluminium end-caps and extruded aluminium profile with powder coating
- Single cable entry
- Stainless steel fasteners in grade 316
- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control

- Up and down light distribution options
- Passive thermal management
- Integral control gear
- Wireless control available through Bluetooth connection

- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

**Optic**



P

**Product colour**



01 - Black (RAL 9011)    03 - White (RAL 9003)    05 - Matt Silver (RAL 9006)

**Special finishes upon request**



SU01 - Concrete - Urban    SU02 - Softscape - Urban    SU03 - Stone - Urban    SU04 - Corten - Urban




SW01 - Oak - Woodland    SW02 - Walnut - Woodland    SW03 - Pine - Woodland

**NYBRO 8 (NYB-30226)**

**Technical information**

<b>Material</b>	Aluminium	<b>Driver option</b>	Integral control gear	<b>CCT / CRI</b>	RGBW40
<b>Light source</b>	192 LED	<b>Driver</b>	Constant current (CC)	<b>Dimming type</b>	Bluetooth
<b>Power</b>	42 W	<b>Input voltage</b>	220-240 V 50/60 Hz	<b>Product colours</b>	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Lumen</b>	2904 lm	<b>Optic</b>	O, P		<b>Weight</b>
<b>Efficacy</b>	69 lm/W	<b>Optic value</b>	Opal, Micro-prismatic	<b>Operating temperature</b>	-20 °C to 40 °C

NYB-30226



**Accessories**



Continuous-coupler bracket  
(60/70 mm Down & 60 mm  
Down & Up profile)  
**A81581**



Xpress wireless switch  
**A90591**



Recessing box  
**A61051**



DALI Control System  
**Control-DALI**