


NYBRO 8 (NYB-30263)



Product description

Down - 60x80 mm - 2906 mm



Luminaire Structure

- Die-cast aluminium end-caps and extruded aluminium profile with powder coating
- Single cable entry
- Stainless steel fasteners in grade 316
- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control

- Up and down light distribution options
- Passive thermal management
- Integral control gear
- Wireless control available through Bluetooth connection

- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)

Optic




P

Product colour



01 - Black (RAL 9011) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)

Special finishes upon request



SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban




SW01 - Oak - Woodland SW02 - Walnut - Woodland SW03 - Pine - Woodland

NYBRO 8 (NYB-30263)

Technical information

| | | | | | |
|----------------------|-----------------------|------------------------|---|--------------------------------|---|
| Material | Aluminium | Input voltage | 220-240 V 50/60 Hz | Operating temperature | -20 °C to 40 °C |
| Light source | 360 LED | Optic | O, P | MacAdam Ellipse | 3 SDCM |
| Power | 92 W | Optic value | Opal, Micro-prismatic | Lifetime L90B10 (hours) | > 23,000 |
| Lumen | 8386 - 10538 lm | CCT / CRI | 3000K CRI80, 4000K CRI80 | Lifetime L80B10 (hours) | > 45,000 |
| Efficacy | 91 - 115 lm/W | Dimming type | On/Off, DALI | Lifetime L80B50 (hours) | > 50,000 |
| Driver option | Integral control gear | Product colours | Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland | Variants (On/Off, DALI) | Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (ZO) |
| Driver | Constant current (CC) | | | | |
| | | Weight | 8.06 kg | | |

NYB-30263




Accessories



Continuous-coupler bracket (60/70 mm Down & 60 mm Down & Up profile)
A81581



Xpress wireless switch
A90591




Wireless bluetooth converter
A90291



Emergency module - 250V - BASIC
EM250V-BA



Emergency module - 250V - PRO-DALI
EM250V-DA



Emergency module - 250V - SELF-TEST
EM250V-ST



DALI Control System
Control-DALI