


## NYBRO 10 (NYB-90257)



### Product description

Down - 60x80 mm - 2330 mm - RGBW DMX



### Luminaire Structure

- Die-cast aluminium end-caps and extruded aluminium profile with powder coating
- Stainless steel fasteners in grade 316
- Single cable entry
- Suspension kit is stainless steel 304 grade, adjustable, suspension (1.5 m) complete with electrical wires in white for mounting
- PMMA diffuser with Opal (UGR <19) and micro prismatic (UGR <13) options for better glare control

- Durable silicone rubber gasket
- Up and downlight distribution options
- Passive thermal management
- Integral control gear
- Wireless control available through Bluetooth connection


- Daylight and occupancy sensor options
- Emergency module (1 or 3 hours) is available upon request with 3 options (BASIC, SELF-TEST, PRO-DALI)
- Track can be integrated into NYBRO products upon request and upon receipt of design drawings

### Optic



P

### Product colour




01 - Black (RAL 9011)

03 - White (RAL 9003)

05 - Matt Silver (RAL 9006)

### Special finishes upon request



SU01 - Concrete - Urban

SU02 - Softscape - Urban

SU03 - Stone - Urban

SU04 - Corten - Urban

SW01 - Oak - Woodland

SW02 - Walnut - Woodland


SW03 - Pine - Woodland

## NYBRO 10 (NYB-90257)


### Technical information

<b>Material</b>	Aluminium	<b>Input voltage</b>	220-240 V 50/60 Hz	<b>Dimming type</b>	DMX, DMX/RDM
<b>Light source</b>	384 LED	<b>Optic</b>	O, P	<b>Product colours</b>	Black, White, Matt Silver, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Power</b>	84 W	<b>CCT / CRI</b>	RGBW40	<b>Weight</b>	6.62 kg
<b>Lumen</b>	5808 lm	<b>Bug</b>	B1-U0-G0, B1-U0-G1	<b>Operating temperature</b>	-20 °C to 40 °C
<b>Efficacy</b>	126 lm/W	<b>ULR</b>	0%	<b>Variants (DMX/RDM)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
<b>Driver option</b>	Integral control gear	<b>ULOR</b>	0%		
<b>Driver</b>	Constant current (CC)	<b>CIE flux code n°3</b>	96, 98		

NYB-90257



### Accessories



Supply cable surface mounting box  
**A80981**



Continuous-coupler bracket  
(60/70 mm Down & 60 mm Down & Up profile)  
**A81581**



Integrated track - 3 phase - DALI for NYBRO  
**A81491**



Integrated track - 3 phase - On-off for NYBRO  
**A81391**



DMX Control System  
**Control-DMX**



DMX/RDM Control System  
**Control-DMX-RDM**