

ODESSA 24 (OD-21092)



Product description

Large - Supplied with specific 6 m cylindrical, tapered galvanised steel pole: SPT160147-OD




Luminaire Structure

- Die-cast aluminium housing
- Pre-treated before powder coating ensuring high corrosion resistance
- Single cable entry
- One cable gland supplied with 2 m of 3x1.0 sqmm outdoor cable

- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- High-efficiency PMMA lens
- Clear toughened glass

- Integral control gear
- Maximum wind load resistance is 160 km/h
- RGBW available upon request

Optic



VN

Product colour




01 - Black (RAL 9011) 02 - Dark Grey (RAL 7043) 03 - White (RAL 9003) 05 - Matt Silver (RAL 9006)



06 - Bronze (RAL 6014)


Special finishes upon request



SU01 - Concrete - Urban SU02 - Softscape - Urban SU03 - Stone - Urban SU04 - Corten - Urban




SW01 - Oak - Woodland SW02 - Walnut - Woodland SW03 - Pine - Woodland

ODESSA 24 (OD-21092)


Honeycomb louvre
A54121



Root mount kit
A20491



Illuminated Beacon-Tip (White
CCT or Single Colour)
A21381



Illuminated Beacon-Tip (RGBW)
A21481

Please contact the factory for technical details if you wish to use Anti-glare accessories, Colour filters, Lenses and slip glasses in combination.