

ODESSA 9 (OD-50112)**Product description**

Thread knuckle mounted – Ø105 mm

**Luminaire Structure**

- Single cable entry
- High-efficiency optical reflector
- Clear toughened glass
- Integral control gear

Optic**M****W****VW****Product colour**

01 - Black (RAL 9011)


02 - Dark Grey (RAL 7043)

03 - White (RAL 9003)

05 - Matt Silver (RAL 9006)



06 - Bronze (RAL 6014)

Special finishes upon request

SU01 - Concrete - Urban

SU02 - Softscape - Urban

SU03 - Stone - Urban

SU04 - Corten - Urban



SW01 - Oak - Woodland



SW02 - Walnut - Woodland



SW03 - Pine - Woodland

ODESSA 9 (OD-50112)

Technical information

Material	Aluminium	Optic value	23°, 32°, 47°	Operating temperature	-20 °C to 40 °C
Light source	1 COB	CCT / CRI	3000K CRI80, 4000K CRI80	Through wiring	Single cable entry
Power	21 W	Bug	B1-U0-G0, B2-U0-G0	Lens / Reflector / Optic	High-efficiency optical reflector, Clear toughened glass
Lumen	1653 - 1688 lm	ULR	0%	MacAdam Ellipse	3 SDCM
Efficacy	79 - 80 lm/W	ULOR	0%	Lifetime L90B10 (hours)	> 109,000
Driver option	Integral control gear	CIE flux code n°3	100	Lifetime L80B10 (hours)	> 109,000
Driver	Constant current (CC)	Dimming type	On/Off, 1-10V, DALI	Lifetime L80B50 (hours)	> 109,000
Input voltage	220-240 V 50/60 Hz	Product colours	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland	Variants (On/Off, 1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Optic	M, W, VW			Weight	

Accessories



Anti-glare visor
A80331



Honeycomb louvre
A80121



Linear spread lens
A80214

Please contact the factory for technical details if you wish to use Anti-glare accessories, Colour filters, Lenses and slip glasses in combination.