


OULU 9 (OUL-90003)**Product description**


Down - 180° - R250 - RGBW

**Luminaire Structure**

- Remote driver (included)

Optic

0


Product colour01 - Black (RAL
9011)03 - White (RAL
9003)05 - Matt Silver
(RAL 9006)**Special finishes upon request**SU01 - Concrete -
UrbanSU02 - Softscape -
UrbanSU03 - Stone -
UrbanSU04 - Corten -
UrbanSW01 - Oak -
WoodlandSW02 - Walnut -
WoodlandSW03 - Pine -
Woodland

OULU 9 (OUL-90003)

Technical information

Material	Aluminium	Driver	Constant current (CC)	Product colours	Black, White, Matt Silver, Concrete
Light source	192 LED	Input voltage	250 mA,		- Urban, Softscape - Urban, Stone
Power	13 W	Optic	0	- Urban, Corten - Urban, Oak -	Woodland, Walnut - Woodland,
Lumen	432 lm	Optic value	Opal	Pine - Woodland	
Efficacy	33 lm/W	CCT / CRI	RGBW40	Weight	2.2 kg
Driver option	Remote driver (included)	Dimming type	Bluetooth	Operating temperature	-20 °C to 40 °C
				Variants (Bluetooth)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)


Oulu 250



Accessories



Continuous-coupler bracket
A81781



Supply cable surface mounting box
A80981



Xpress wireless switch
A90591



DALI Control System
Control-DALI