

**PALETTA 5 (PA-31944)**



**Product description**

355x355 mm - TW



**Luminaire Structure**

- Die-cast aluminium housing and frame
- Pre-treated before powder coating ensuring high corrosion resistance
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Opal UV-stabilised polycarbonate diffuser
- Integral control gear
- Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible

**Optic**



G

**Product colour**




01 - Black (RAL 9011)    02 - Dark Grey (RAL 7043)    03 - White (RAL 9003)    05 - Matt Silver (RAL 9006)



06 - Bronze (RAL 6014)

**Special finishes upon request**




SU01 - Concrete - Urban    SU02 - Softscape - Urban    SU03 - Stone - Urban    SU04 - Corten - Urban



SW01 - Oak - Woodland



SW02 - Walnut - Woodland




SW03 - Pine - Woodland

**PALETTA 5 (PA-31944)**

**Technical information**

<b>Material</b>	Aluminium	<b>Input voltage</b>	220-240 V 50/60 Hz	<b>CIE flux code n°3</b>	92
<b>Light source</b>	192 LED	<b>Optic</b>	G	<b>Dimming type</b>	DALI
<b>Power</b>	28 W	<b>Optic value</b>	123°x123°	<b>Product colours</b>	Black, Dark Grey, White, Matt Silver, Bronze, Concrete - Urban, Softscape - Urban, Stone - Urban, Corten - Urban, Oak - Woodland, Walnut - Woodland, Pine - Woodland
<b>Lumen</b>	2258 lm	<b>CCT / CRI</b>	TW (2700K - 6500K)		
<b>Efficacy</b>	81 lm/W	<b>Bug</b>	B1-U3-G1		
<b>Driver option</b>	Integral control gear	<b>ULR</b>	5.5%	<b>Weight</b>	4.8 kg
<b>Driver</b>	Constant current (CC)	<b>ULOR</b>	5.5%	<b>Through wiring</b>	Two cable entries for through wiring
				<b>Lens / Reflector / Optic</b>	Opal UV-stabilised polycarbonate diffuser

PA-31944



**Accessories**



Surface mounting box for easy cabling (PALETTA 5)  
**SCE-PALETTA-5**