

PATCHI 2 (PAT-30031) (Version 1)



Product description

Without remote driver - Constant voltage (CV) 24 V - RGBW dynamic programming - 32 addresses/channels - 28x42.9 mm - 1000 mm



Luminaire Structure


- Aluminium anodised housing
- Spring snap-on mounting bracket, easy installing and aiming
- Two cable entries for through wiring
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Opal PMMA curved diffuser
- Remote driver (not included)
- Uniform light distribution with uninterrupted end-to-end mounting.
- $\geq 90^\circ$ viewing angle
- 24 VDC input, DMX512 address with stable signal

Optic



EW

Product colour



05 - Matt Silver (RAL 9006)

PATCHI 2 (PAT-30031) (Version 1)

Technical information

Material	Aluminium
Light source	48 LED
Power	13 W
Lumen	195 - 198 lm
Efficacy	15 lm/W
Driver option	Remote driver (not included)

Driver	Constant voltage (CV)
Input voltage	24 VDC
Optic	EW
Optic value	115°
CCT / CRI	RGBW30, RGBW40
Dimming type	DMX

Product colours	Matt Silver
Weight	0.6 kg
Operating temperature	-20 °C to 40 °C
Through wiring	Two cable entries for through wiring
Lens / Reflector / Optic	Opal PMMA curved diffuser

PAT-30031



PATCHI 2 (PAT-30031) (Version 1)**Accessory**

DMX Control System
Control-DMX



Driver (CV) - On/Off - 36 W - IP67
- 24 V
A34491-ND



Driver (CV) - On/Off - 60 W - IP67
- 24 V
A34591-ND



Driver (CV) - On/Off - 100 W -
IP67 - 24 V
A34791-ND



Driver (CV) - On/Off - 150 W -
IP67 - 24 V
A34891-ND



Driver (CV) - On/Off - 200 W -
IP67 - 24 V
A34991-ND



Driver (CV) - On/Off - 350 W -
IP67 - 24 V
A35091-ND