

**PERTH 1 (PER-80001)****Product description**

Without remote driver - Constant current (CC) 350 mA  
- Ø50 mm - 46.5 mm - 6 W LED Module

**Luminaire Structure**

- Lamp modules with different trim options  
- Trim is a required accessory, please choose one

- Trims are White (03- RAL9003) as standard,  
Black is (01-RAL9011) upon request  
- Remote driver (not included)

- Standard: 3000K (2700K and 4000K available upon request)

**Optic**

C

F

**Product colour**


03 - White (RAL  
9003)

**PERTH 1 (PER-80001)**

**Technical information**

<b>Material</b>	Aluminium	<b>Driver</b>	Constant current (CC)	<b>Product colours</b>	White
<b>Light source</b>	1 COB	<b>Input voltage</b>	350 mA, 13-26 VDC	<b>Weight</b>	0.08 kg
<b>Power</b>	6 W	<b>Optic</b>	C, F	<b>Operating temperature</b>	-20 °C to 40 °C
<b>Lumen</b>	522 - 555 lm	<b>Optic value</b>	49°, 56°	<b>Variants (1-10V, DALI)</b>	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
<b>Efficacy</b>	87 - 93 lm/W	<b>CCT / CRI</b>	3000K CRI90		
<b>Driver option</b>	Remote driver (not included)	<b>Dimming type</b>	On/Off, 1-10V, DALI		

**PER-80001**



**Accessories**



Trim - Deep recessed (White)  
**A80001-M3W**



Trim - Deep recessed directional (White)  
**A80001-M5W**



Trim - Curve recessed (White)  
**A80001-M8W**



Trim - Key hole IP44 (White)  
**A80001-D5W**



Trim - Pin hole IP44 (White)  
**A80001-D4W**



Trim - Shallow directional (White)  
**A80001-M7W**



Trim - Shallow IP44 (White)  
**A80001-M1W**



Trim - Surface cylinder (White)  
**A80001-C135W**

**PERTH 1** (PER-80001)



DALI Control System  
**Control-DALI**

---