

PERTH 2 (PER-80002)



Product description


Without remote driver - Constant current (CC) 260 mA
- Ø66 mm - 70 mm - 9 W LED Module



Luminaire Structure

- Lamp modules with different trim options
- Trim is a required accessory, please choose one
- Trims are White (03- RAL9003) as standard, Black is (01-RAL9011) upon request
- Remote driver (not included)
- Standard: 3000K (2700K and 4000K available upon request)

Optic



C

F

Product colour




00 - Stainless Steel

PERTH 2 (PER-80002)

Technical information

Material	Stainless Steel	Driver	Constant current (CC)	Product colours	Stainless Steel
Light source	1 COB	Input voltage	260 mA, 23-46 VDC	Weight	0.11 kg
Power	9 W	Optic	C, F	Operating temperature	-20 °C to 40 °C
Lumen	787 - 943 lm	Optic value	53°, 59°	Variants (1-10V, DALI)	Compatible with EN/ IEC 60598-2-22: Suitable for emergency installations as central supply, non-maintained (Z0)
Efficacy	87 - 105 lm/W	CCT / CRI	3000K CRI90		
Driver option	Remote driver (not included)	Dimming type	On/Off, 1-10V, DALI		

PER-80002



Accessories



Trim - Deep recessed (White)
A80001-M3W



Trim - Deep recessed directional (White)
A80001-M5W



Trim - Curve recessed (White)
A80001-M8W



Trim - Key hole IP44 (White)
A80001-D5W



Trim - Pin hole IP44 (White)
A80001-D4W



Trim - Shallow directional (White)
A80001-M7W



Trim - Shallow IP44 (White)
A80001-M1W



Trim - Surface cylinder (White)
A80001-C135W

PERTH 2 (PER-80002)



DALI Control System
Control-DALI