

PETRA 1 (PET-60001)**Product description**

Ø120 - With recessing box - With driver

**Luminaire Structure**

- Casting brass housing
- 6 mm thick front ring in brass
- Single cable entry, through wiring upon request
- One cable gland supplied with 1.5 m of 3x1.0 sqmm outdoor cable
- Stainless steel fasteners in grade 304 with zinc flake coating (ZFC)
- Durable silicone rubber gasket
- Clear toughened glass
- Integral control gear
- Recessing box in high-density polyethylene is included
- Suitable for walk-over with a maximum load of 200 kg

Optic**Product colour**

99 - Brass

PETRA 1 (PET-60001)

Technical information

Material	Brass
Light source	MR16-GU10
Power	8 W
Lumen	369 - 455 lm
Efficacy	49 - 61 lm/W
Driver option	Integral control gear
Driver	Constant current (CC)
Input voltage	220-240 V 50/60 Hz

Optic	N, M, VW, E
Optic value	10°, 25°, 60°, 10°x60°
CCT / CRI	3000K CRI80, 4000K CRI80
Bug	B0-U1-G0, B1-U0-G0
ULR	<1%
ULOR	<1%
CIE flux code n°3	97, 98
Dimming type	On/Off

Product colours	Brass
Weight	2.2 kg
Operating temperature	-20 °C to 40 °C
Cable	One cable gland supplied with 1.5 m of 3x1.0 sqmm outdoor cable
Through wiring	Single cable entry, through wiring upon request
Lens / Reflector / Optic	Clear toughened glass

PET-60001

